

OS-1W White (85 Lm, 6000K)


Features

- Highest Luminous Flux
- Super Energy Efficiency
- Long Lifetime Operation
- Superior ESD protection
- Superior UV Resistance

Applications

- Read lights (car, bus, aircraft)
- Portable (flashlight, bicycle)
- Bollards / Security / Garden
- Traffic signaling / Beacons
- In door / Out door Commercial lights
- Automotive Ext

Outline Dimension



Absolute Maximum Rating


Item	Symbol	Value	Unit
DC Forward Current	IF	400	mA
Pulse Forward Current*	IFP	500	mA
Reverse Voltage	VR	5	V
Power Dissipation	PD	1600	mW
Operating Temperature	Topr	-30 ~ +85	°C
Storage Temperature	Tstg	-40~ +100	°C
Lead Soldering Temperature	Tsol	260 °C /5sec	-

Notes: *Pulse width Max.10ms Duty ratio max 1/10

Typical Electrical / Optical Characteristics at TA=25°C

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
DC Forward Voltage	VF	IF=350mA	3.0	3.3	4.0	V
DC Reverse Current	IR	VR=5V	-	-	10	μA
Luminous Flux	φv	IF=350mA	75	85	-	lm
Color Temperature	CCT	IF=350mA	-	6500	-	K
Chromaticity Coordinates*	x	IF=350mA	-	0.31	-	
	y	IF=350mA	-	0.33	-	
50% Power Angle	2θ1/2	IF=350mA	-	120	-	deg

Directivity



Forward Operating Current (DC)

