




REACH
The new EU chemicals legislation



ATTENTION
OBSERVE PRECAUTIONS
ELECTROSTATIC
SENSITIVE DEVICES

arlight

OS-3W WarmWhite (180 Lm, 3000K)




Features

- Highest Luminous Flux
- Super Energy Efficiency
- Long Lifetime Operation
- Superior ESD protection
- Superior UV Resistance

Applications

- Read lights (car, bus, aircraft)
- Portable (flashlight, bicycle)
- Bollards / Security / Garden
- Traffic signaling / Beacons
- In door / Out door Commercial lights
- Automotive Ext

Outline Dimension



Absolute Maximum Rating

Item	Symbol	Value	Unit
DC Forward Current	IF	800	mA
Pulse Forward Current*	IFP	1000	mA
Reverse Voltage	VR	5	V
Power Dissipation	PD	3200	mW
Operating Temperature	Topr	-30 ~ +85	°C
Storage Temperature	Tstg	-40~ +100	°C
Lead Soldering Temperature	Tsol	260°C /5sec	


Notes: *Pulse width Max.10ms Duty ratio max 1/10

Typical Electrical / Optical Characteristics at TA=25°C

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
DC Forward Voltage	VF	IF=700mA	3.0	3.3	4.0	V
DC Reverse Current	IR	VR=5V	-	-	10	µA
Luminous Flux	Φv	IF=700mA	160	180	-	lm
Color Temperature	CCT	IF=700mA	-	3000	-	K
Chromaticity Coordinates*	x	IF=700mA	-	0.45	-	-
	y	IF=700mA	-	0.41	-	-
50% Power Angle	2θ1/2	IF=700mA	-	120	-	deg

Note: Don't drive at rated current more than 5s without heat sink for Xeon 1 emitter series.

Directivity



Forward Operating Current (DC)

